CN	AW	
www. 800	CNAweb. 0.516.126	

Analog/AHD DVRs



Our Analog/AHD Cameras work with legacy Analog (CVBS) and new **AHD** systems!

3.6mm Fixed Lens Day/Night

1/3" Color **Domes**



All aluminum indoor/outdoor vandal-proof housing. Built-in OSD with 3-axis bracket. 65' (5x24ir) night vision, IP65, with BNC and 12V DC power connectors.

604499 1/3" CMOS, 800 TVL, 960H, D1, White 23.00 23.00 604485 1/3" CMOS, 800 TVL, 960H, D1, Gray 29.00 604597 1/3" Sony, 1000 TVL, 960H, D1, White 29.00 604601 1/3" Sony, 1000TVL, 960H, D1, Grav 404794 AHD 1/3" Sony, 1.3MP, 720P, 960H, White 37.00 404806 AHD 1/3" Sony, 1.3MP, 720P, 960H, Gray 37.00

1/3" 2.8-12mm Vari-Focal Day/Night

Domes



2.8~12mm color Vari-Focal Lens for flexible mounting locations. All aluminum indoor/outdoor vandal-proof housing. Built-in OSD with 3-axis bracket. 100' (5x36ir) Night Vision, IP65, DWDR, with BNC and 12V DC power connectors. 404808 AHD 1/3" Sony, 1.3MP, 720P, 960H, White 49.00 404803 AHD 1/3" Sony, 1.3MP, 720P, 960H, Gray 49.00

2.8~12mm Vari-Focal Day/Night Color Dome

All aluminum indoor/outdoor vandal-proof housing. Built-in OSD with 3-axis bracket. 100' night vision, IP66, with BNC and 12V DC Power connectors.



604599 1/3" Sony, 1000 TVL, 960H, D1, White 59.00 404801 AHD 1/3" Sony, 1.3MP, 720P, 960H, low-light DWDR, 3DNR, Sense-up, White 79.00

Day/Night Bullet Cameras

3.6mm 1/3" Color Lens, with OSD Weatherproof aluminium IP66 housing with 12V DC power. 65' (5x24ir) night vision. 604798 1/3" CMOS, 800TVL, 960H, D1 404802 AHD 1/3" Sony, 1.3MP, 720P, 960H

Day/Night Bullet Cameras

3.6mm 1/3" Color Lens, with OSD. Weatherproof aluminium IP66 housing with12V DC Power. 65' (5x24ir) Night Vision. CNA# 604482 1/3" CMOS, 800 TVL, 960H, D1 28.00 604608 1/3" Sony, 1000 TVL, 960H, D1 34.00 39.00 404800 AHD 1/3" Sony, 1.3MP, 720P, 960H

28.00

39.00

1/3" Color Vari-Focal Day/Night **Bullet Cameras**

2.8~12mm vari-focal Lens, 720P, OSD Weatherproof aluminium IP66 housing with12V DC power. 200' (5x72ir) night vision. 404805 AHD 1/3" Sony, 1.3MP, 720P, 960H 59.00

12V DC Power Adapters

UL Listed AC/DC Adapter with 5.5 x 2.1MM Barrel Connector, tip positive plug. 2.90 88-681 12V DC, 500 mA 88-672 12V DC, 1000 mA 3.90 500926 12V DC, 2000 mA 5.90

12V DC 5A Power Adapter

UL Listed AC/DC Adapter with 5.5 x 2.1MM Barrel Connector, tip positive plug.

CNA# 500930 12V DC, 5000 mA 11.90

Camera Power Splitter

Allows the connection of multiple cameras to the same power supply. CNA# DP-4 4 Way camera 5.5 x 2.1mm splitter DP-8 8 Way camera 5.5 x 2.1mm splitter

CCTV Extension Cables

Extends Video (BNC Male to Male) and Power (2.1MM Coax Male to Female) CNA# 7.90 503015 65 ft. 9.90 503020 100 ft.

Network PoE 10/100

Switches

604856 5-Port with 4-Port PoE, 48 Watts 604858 9-Port with 8-Port PoE, 96 Watts

PoE Splitter

The PoE adapter cable kit is designed to allow power to be delivered alongside data, over a single ethernet cable, to an ethernet enabled device up to 300' (100m) away. CNA# 604671 Pair 4.75



Network Video Recorders (NVR)



12V DC power connector.

604927 1/2.9" Sony, 2.4MP , 1080P, WDR, White 99.00 604926 1/2.9" Sony, 2.4MP , 1080P, WDR, Gray 99.00

IP-HD2.8~12mm Vari-Focal Day/Night Color

Cameras



IP-HD 2.8~12mm color Vari-Focal Lens for flexible mounting locations. All aluminum indoor/outdoor vandalproof housings. 100' (5x36ir) Night Vision, IP65, with POE and 12V DC power connector. CNA#

604929 1/2.9" Sony, 2.4MP , 1080P, WDR, Gray 99.00 404590 1/2.9" Sony, 2.4MP , 1080P, WDR, White 129.00







68.50 118.50





Cat5e, 350 MHz **Molded Patch** Cables

43-742 GR

UTP 'Ferari' style RJ45 patch cables 35 (8P8C), L gigabit et plated 50 round sna protects t from dam CNA#



9.75

8.90

cables 350MH (8P8C), UL Lis gigabit etherne plated 50u, 24 round snagless	sted 10/100 and et networks. Gold IAWG stranded, s 'Ferari' molding		•
protects the R from damage	J45 plastic tab during installation		ST 1988
CNA#		1-9	10+
43-715 xx	1 ft.	.95	.75
43-720 xx	3 ft.	1.05	.90
43-723 xx	5 ft.	1.15	1.05
43-725 xx	7 ft.	1.70	1.35
43-727 xx	10 ft.	2.00	1.70
43-730 xx	15 ft.	2.60	2.20
43-735 xx	25 ft.	3.80	3.30
43-740 xx	50 ft.	6.50	5.90
10 710		0.75	

43-745 xx	100 ft.	12.75	11.90
	XX = Use color code I	below	
GR BK	BL GN OR	PR RD	<mark>│</mark> YL

UL Listed 110 Type

75 ft.

Keystone Jacks Meet EIA/TIA Cat5e standard Gold plated contacts T568Å/T568B EIA/TIA standard 23-26 AWG network cable CNA# 1-9 10 +43-309 xx RJ45, Cat5e 1.15 .85 1.55 1.10 43-312 xx RJ45, Cat6 XX = Use color code below

IV WH BK BL GN OR RD YL

Keystone Modular Smooth Face Wall Plates w/Hardwaro

W/ naruw	are				
CNA#		Provide States		1-9	10+
604024 xx	Single	Cavity Plate	е	.49	.39
604026 xx	Dual C	avity Plate		.49	.39
604028 xx	Three	Cavity Plate	Э	.49	.39
604030 xx	Four C	avity Plate		.49	.39
604032 xx	Six Ca	vity Plate		.49	.39
43-239 xx	Blank (Cavity Cover		.35	.25
	XX =	Use color c	ode helow		

Jse color code below WH IV

Network RJ45

Couplers	
Great for	

Great for extending CNA#	cables.		Carac	1-4	5+
602009	(A) Cat5	Keystone,	White	1.25	.90
602690		Keystone,		1.25	.90
602689	(A) Cat6	Keystone,	White	1.75	1.25
602687	(A) Cat6	Keystone,	Black	1.75	1.25
		-			

19" Equipment Wall Mount **Brackets**

CNA#	B	
43-617A	1U Hinged Wall Mount 7" Depth	8.75
43-629A	2U Hinged Wall Mount 7" Depth	10.50
43-613A	4U Hinged Wall Mount 12" Depth	19.75
	7U Hinged Wall Mount 12" Depth	29.50

Cat5e/6 Patch Panels

110 type wiring Cat5e certified

To type winng, Galbe centiled.				
UL listed.	Supervised Control of Statement of Supervised			
CNA#	Consideral Relational Balanceara (Consideration)			
43-612	12 Port T568B, 1-3/4" High (1U)	14.90		
43-624	24 Port T568B, 1-3/4" High (1U)	19.90		
43-648	48 Port T568B, 3-1/2" High (2U)	39.00		
43-696	96 Port T568B, 7" High (4U)	79.00		
Cat6 Patc	h Panels			
43-630	12 Port T568B, 1-3/4" High (1U)	17.50		
43-626	24 Port T568B, 1-3/4" High (1U)	23.75		
43-632	48 Port T568B, 3-1/2" High (2U)	44.00		
43-622	96 Port T568B, 7" High (4U)	89.00		



19" Rack Vented Shelves

		and a second				
	The vented equipment shelves					
	ned for 19" rack mount					
widths. T	he 1-piece design					
allows for	strong support.	*				
Finished	in durable black	/				
powder c	oat.					
43-671	11" Single-Sided Cantilever Shelf (1U)	13.75				
	15" Single-Sided Cantilever Shelf (2U)	18.50				
43-678	19" Double-Sided Center Shelf (2U)	27.50				
43-672	25" Double-Sided Center Shelf (2U)	59.75				

19" Simple Vertical Back

	pie vertical flack	
weight verti- design intell cost effectiv solution for equipment. steel constru- compatible rack mounta Mounts easi	Rack's light- cal wall mount igently produces a e and space saving your IT and AV Durable solid uction and is with nearly all 19" able equipment. ly to walls, desks ertical surfaces.	
604811 604835 604842	1U (2.5" Deep) Wall Mount 2U (3.5" Deep) Wall Mount 3U (5.25" Deep) Wall Mount 4U (7" Deep) Wall Mount	14.75 19.75 23.00 28.75

www.CNAweb.com


Super VGA UL2919 3 Coax Monitor Cables DB15(HD)						
85-174	6 ft.	Male t	o Male	5.50	5.10	
85-173	6 ft.	Male t	to Female	5.50	5.10	
85-081	10 ft.	Male t	o Male	6.50	5.90	
85-085	10 ft.	Male t	to Female	6.50	5.90	
85-182	15 ft.	Male t	o Male	8.50	7.90	
85-187	15 ft.	Male t	to Female	8.50	7.90	
85-189	25 ft.	Male t	o Male	12.20	11.50	
85-190	25 ft.	Male t	to Female	12.20	11.50	
85-192	50 ft.	Male t	o Male	20.90	19.90	
85-195	50 ft.	Male t	to Female	20.90	19.90	
85-210	75 ft.	Male t	o Male	30.90	28.90	
85-214	75 ft.	Male t	to Female	30.90	28.90	
85-222	100 ft	. Male t	o Male	39.50	37.00	
85-213	100 ft	. Male t	to Female	39.50	37.00	

6 Outlet Plastic Strip Surge Protector, White

		.,			
Includes circuit breaker, on/off switch, high impact flame					
	plastic hous				
		•			
(AC 125V/	15A, UL/CSA	listed,	1MOV)		
CNA#		1-4	5+		
89-015	3 ft. Cord	3.90	3.40		
215051	1.5 ft. Cord	3.90	3.80		
215002	6 ft. Cord	6.25	5.90		
215010	12 ft.Cord	8.95	8.50		

6 Outlet Plastic Strip Surge Protector, Black Includes circuit breaker and high-impact flame retardant	K Contraction	
plastic housing. 89-018 3' Cord, Black 215002BK 6' Cord, Black	1-4 3.90 6.25	
3 Outlet Mini Power Strip with 1 ft. Cord AC 125V/13A. UL listed. CNA# 215024 UL Approved	1-4 2.25	5+ 1.95

23~63" LCD/Plasma/TV Mounts



HDMI Cables

High-spee HDMI with HDMI v1.	h etherr				-		\bigcirc
CNA#		STATES.			and a	1-4	5+
72-772	3 ft.	HDMI	Male	to	Male	2.50	1.90
72-776	6 ft.	HDMI	Male	to	Male	3.60	2.90
72-771	10 ft.	HDMI	Male	to	Male	4.80	3.90
72-770	15 ft.	HDMI	Male	to	Male	5.90	5.00
181205	20 ft.	HDMI	Male	to	Male	9.50	8.50
181206	30 ft.	HDMI	Male	to	Male	20.90	18.90
181207	50 ft.	HDMI	Male	to	Male	31.50	29.00
181208	75 ft.	HDMI	Male	to	Male	52.00	49.00
181209	100 ft.	HDMI	Male	to	Male	80.50	75.00
604392	1.5 ft.	Thin H	IDMI	M	to M	3.90	3.40
604202	3 ft.	Thin H	IDMI	M	to M	4.75	4.25
604203	6 ft.	Thin H	IDMI	M	to M	5.90	5.25

HDMI



181243 HDMI Male to Female Right Angle 181260 HDMI Male to Female 180 Degree

1.90 1.90 2.90

Bulk Security Cable Siamese Coaxial and Power 72-065 RG59 Siamese Coaxial with 18 AWG Power Pair, 95%, 500ft., Black 59.00 202609WH RG59 Siamese Coaxial with 18 AWG Power Pair, 95%, 500ft., White 59.00 CNA# 96.00 202605 RG59 Siamese Coaxial with 18 AWG Power Pair. 95%. 1000ft., Black 82-143 202606 RG59 Siamese Coaxial with 18 AWG Power Pair, 95%, 1000ft., White 96.00 82-139 RG59 Coaxial with 18 AWG Power Pair, Direct Burial, 95%, 1000ft., Black 165.00 604413 RACEWAY

Raceway with Adhesive Backing





6 ft. Raceway Section 3/4" 1-1/4" 6 ft. Raceway Section А 6 ft. Raceway Section 1-3/4"

CNA# 10up 1-9 43-757xx 6.95 6.75 43-117xx 10.10 9.50 43-177xx 14.40 13.90



The one piece design construction of 94V-O rigid vinyl, features a highly flexible hinge and self-locking latch. Available in Office White, White(WH) and Ivory(IV).

			/-	
Bulk Net	work Cable			
UTP Solid	1			alle care in
83-407	Cat5e, CMR, PVC, 350 MHz, 24 AWG, Solid, 1000ft., Gray	79.50		
83-407B	Cat5e, CMR, PVC, 350 MHz, 24 AWG, Solid, 1000ft., Blue	79.50	-	
83-407ĸ	Cat5e, CMR, PVC, 350 MHz, 24 AWG, Solid, 1000ft., Black	79.50		
83-402	Cat6e, CMR, PVC, 550 MHz, 23 AWG, Solid, 1000ft., Gray	119.00		
83-402B	Cat6e, CMR, PVC, 550 MHz, 23 AWG, Solid, 1000ft., Blue	119.00		/
83-402ĸ	Cat6e, CMR, PVC, 550 MHz, 23 AWG, Solid, 1000ft., Black	119.00		
UTP Plenu	um Solid		-	
82-927WH	Cat5e, CMP, Plenum 350 MHz, 24 AWG, Solid, 1000ft., White	179.00	ALLAL MARALINE	
82-927BL	Cat5e, CMP, Plenum 350 MHz, 24 AWG, Solid, 1000ft., Blue	179.00	termanue	51
83-406	Cat6e, CMP, Plenum, 550 MHz, 23 AWG, Solid, 1000ft., Grav	259.00	*	1
Outdoor L	Direct Burial Solid			/
83-415	Cat5e, PE, 350 MHz, Outdoor, Direct Burial, Solid, 1000ft., Black	145.00		
	· · · · · · · · · · · · · · · · · · ·			

USB Headphones w/ Microphone

In-line function control button with volume up, volume down and mute. CNA# 603800

Lightweight Digital Stereo Headphones

Foam ear cushions for wide range sound. Cord length: 4' 1.89 603911 Black 603912 White 1.89

Deluxe Earbud Headphones

Comfort fit with unique design. Compatible with MP3 players and cell phones. 3.5mm stereo plug with 1.2m cord. 604101BK Black 1.29 604101WT White 1.29

www.CNAweb.com

9.95

Enhanced Keyboard



Features 3 Special Windows Keys. High quality keyswitch with tactile touch. A streamlined design with a small footprint. 310214 USB, Black 5.90 **USB 2.0 Active Cables**

Lengthen USB device cable with the active USB 2.0 compliant extension cable. 16 ft. A to A M-F Extension 85-664 603763 30 ft. A to A M-F Extension

13.75 21.25 604067 50 ft. A to A M-F Extension 604068 65 ft. A to A M-F Extension 27.50 604069 80 ft. A to A M-F Extension 32.00 603764 30 ft. A Male to B Male 14.50

Cell **USB 2.0** Phones A to Micro B and Tablets Cables 150148 8 in. A Male to Micro B Male .59 150149 .69 3 ft. A Male to Micro B Male .99 150150 6 ft. A Male to Micro B Male

USB 150 Ft. Extender Via Cat5 Ethernet

Allows a USB device to have its cable length extended up to 150 Ft. No driver needed. LAN cable required: Cat.5/5E/6 150443

USB Economy Optical Mouse

High-precision optical sensor design with 800dpi. Programmable button for easy web surfing and document reading. 603400 USB. Black



BNC Compression Connector



Ratchet Type Cable Crimping Tool

9" Hex crimp tool for RG58, RG59, RG62 and RG6 fittings and center pin. Full cycle ratchet mechanism. 72-005

Coaxial Stripping Tool

Rotary Coaxial Cable Stripper for RG6, RG58, and RG59 604819

3.90

19.75

.39

.68

RJ45 Modular Data Plugs

12.75

11.25

3.90

CNA# 83-368 83-468	RJ45, Cat5e, 8P8C, 50 Micron Solid 3-Prong, 100pcs Stranded 2-Prong, 100pcs	9.90 8.90
CNA# 83-478 83-475	RJ45, Cat6, 8P8C, 50 Micron Solid 2-Prong, 100pcs Solid 3-Prong w/ Inserter, 100pcs	9.90 10.90

4P/6P/8P Network & Telephone

Cable Crimping Tool

Designed for use with RJ9/RJ10/RJ11/RJ-22/(4P), RJ12/(6P) and RJ45(8P) modular UTP/STP cables and connectors. CNA# 604839



UTP Jacket Stripper

Universal stripping tool for multi-conductor cable from 3.5 mm to 9 mm. 84-300




Custom Printed Domed



Quality, full color, clear, domed custom product logos. Crystal clear, dimensional, highly flexible dome protects your logo from wear and tear indoors and outdoors. High-adhesion selfadhesive - our labels stick. Great for all types of custom products: electronics, computers, appliances, cell phones, ad specialties, power tools, toys and packaging. Domed logos are everywhere in the product branding and servicing industries. Email your logo design to sales@cnaweb.com after ordering. We accept all file formate

ionnais.
CNA#
85-762



1 3 2 3



www.CNAweb.com 800-516-1262

12 VDC

Adapter: starting at

\$2⁹⁰

UL Cat5e Jacks

85¢

starting at

24 UL Patch Panels^{\$}19⁹⁰

Over 3000 products online at CNAweb.com!

DVRs & NVRs

starting at

\$59⁰⁰